

Model IQ 560E

Multi-functional telephone

Available in a Telephone & Headset Pack



Feature List

- Adjustable Headset hearing level with slider volume control
- Noise cancelling handset microphone
- Mute key & Indicator
- Full Six (6) Year warranty
- Redial and Pause functions
- Ringer volume and pitch controls
- Handsfree speaker with volume control
- Built-in Data Port for peripheral devices
- Built-in headset support – external headset amplifiers are not required, providing a considerable cost saving when using a headset
- 16 digit LCD display with clock and timer
- Built-in trainee/supervisor "double jacking" mode
- Acoustic Shock Protection for handset and headset
- 20 memories, 10 of which can be factory-programmed
- "Silent Ringing" allows ringing to be heard in headset only
- Mid-call mode support (change between Headset, Handsfree and Handset during a call)
- Built-in message waiting and super bright LED ringer indicator lamp
- Eeprom Memory supports definable soft-keys for configurable system or network feature access



Interquartz Warranty
6 Years
Parts and Labour



| Brief Specifications of Interquartz IQ 560E | |
|---|---|
| Dial mode | Tone (DTMF) |
| 20 Memory Buttons | 32 digits each |
| Pause | 2 Seconds |
| PBXRecall | 100 milliseconds Timed Break |
| Memory Retention | Non-volatile memory (permanent retention without power) |
| Power Source | Line powered. Batteries NOT required |
| Redial function | 32 digits |
| Ringer Lamp | Superbright LED and Neon tube |
| Message Waiting light | Suits: Ericsson BP250, Alcatel, Exicom, Fujitsu, NEC, Nortel, Samsung, Lucent Index and Hybrex Optional: AT&T, Siemens ISDX, Siemens HICOM, Panasonic TD1232, Ericsson MD110 and some Hybrex |
| Dimensions | Width: 169mm; Length: 225mm; Height: 90mm |
| Ringer | Electronic, with Hi/Lo/Off settings; 80dBA at 1 Ft |
| Line cord and Plug | 3m RJ12 to RJ45 line cord with optional 603, RJ11 or RJ12 on request |
| Wall mount kit | Wall Mount Kit No.3 (Order separately) |
| Operating Temp and Humidity | Temperature : 0°C - 40°C; Humidity : 95% RH max, No dew forming |
| Regulatory Compliance | Complies with current ACA/Austel standards |
| Acoustic Shock Protection | Instantaneous – less than 100dB SPL (ACA standard 123dB SPL) Continuous – 104dBA (ACA standard 120dBA) |
| Colour | Black or Granite Grey – ABS Plastic |